

Material Safety Data Sheet U. S. Department of Labor

May be used to comply with Occupational Safety and Health Administration
OSHA's Hazard Communication Standard, (Non-Mandatory Form)
29 CFR 1910.1200. Standard must be Form Approved
consulted for specific requirements. OMB No. 1218-0072

IDENTIFY (As used on label) NN Advanced Formula Resin 1oz.	
Section I	
Manufacture's Name PNI WorldWide	Emergency Telephone Number 1-800-535-5053 (International Number) 813-960-2780
Address (Number, Street, City, State and ZIP Code)	Telephone Number for Information SAA
5454 West Crenshaw Street	Data Prepared 03-22-07
Tampa, Fl 33634	
Section II – Hazardous Ingredients/Identity Information	
Hazardous Components (Specify Chemical Identity: Common Name(s) OSHA PEL ACGIH TLV Other Limits Recommended (% Optional)	
HMIS Hazard Rating: Health 2 (moderate) Flammability 2 (moderate) Physical hazard 1 (slight)	
Ethyl cyanoacrylate 7085-85-0 80-100% OSHA PEL (None) ACGIH (TWA) 0.2ppm	

Poly (methyl methacrylate) 9011-14-7 5-10%

Butylated Hydroxy Anisole* 25013-16-5 0.1-0.2%

* Prop 65 Chemical (No significant risk level 4,000 micrograms/day.)

Section III – Physical/Chemical Characteristics

Boiling Point	> 300 °F	Specific Gravity (H2O =1)	~1.05
Vapor Pressure (mm Hg)	< 0.2 mm Hg @ 75 °F	Melting Point	Not Determined
Vapor Density (AIR = 1)	Approximately 3	Evaporation Rate (Butyl Acetate = 1)	Not Determined

Solubility in Water : Polymerizes in the presence of water

Appearance and Odor: Clear Liquid with sharp irritating odor (Odor Threshold: 1-2ppm)

Percent Volatile, by volume: Less than 20g/l (California SCAQMD method 316B)

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used)	176 - 200°F (T.C.C.)	Flammable Limits	LEL N/A	UEL N/A
---------------------------	----------------------	------------------	---------	---------

Extinguishing Media: Dry chemical, Foam, Carbon dioxide Auto-ignition Temperature: ~905°F

Special Fire Fighting Procedures: Full protective equipment including Self Contained Breathing Apparatus is recommended

Unusual Fire and Explosion Hazards. Irritating organic vapors

Section V – Health Hazard Data

Threshold Limit Value: Ethyl Cyanoacrylate 0.2ppm TWA(ACGIH); Butylated Hydroxyanisole 2mg/m³ TWA (ACGIH) and OSHA(PEL).

Ingestion: Ingestion is not likely. The product will polymerize rapidly, adhering to the mouth. Ensure breathing passages are clear. Saliva will separate any solidified product within two days. Prevent accidental swallowing.

Skin: bonds skin rapidly and strongly and may cause burns. Soak affected area with warm soapy water. Gently peel bonded skin, DO NOT PULL SKIN APART. If skin is burned by a large drop (due to heat generated by the polymerization) seek medical help. If lips are accidentally bonded, apply warm soapy water, encourage maximum wetting and pressure from saliva inside the mouth and peel or roll lips apart. DO NOT TRY TO PULL LIPS APART.

Inhalation: May be irritating to respiratory system above recommended exposure limits. Remove to fresh air. If breathing is difficult seek medical attention. Prolonged and repeated overexposure to vapors may produce non-allergic asthma in sensitive individuals.

Eyes: Irritating to eyes. Immediately flush eyes with plenty of water for at least 15 minutes and get prompt medical attention. If eyelids are bonded closed, cover with a wet pad. DO NOT FORCE EYES OPEN. Cyanoacrylate will bond to eye protein and cause a lachrymatory effect which will help de-bond the adhesive. Keep eye covered until de-bonding is complete (usually 1-4 days).

Carcinogenicity Inds: BHA: NTP: Yes, IARC: 2B, OSHA: NO

Section VI – Reactivity Data

Stability	Unstable		Elevated temperatures, direct sunlight, and sources of ignition.
	Stable	X	Stable under recommended storage conditions.

Incompatibility (*Materials to avoid*) Polymerization initiators: water, amines, alkali and alcohol.

Section VI – Reactivity Data (cont)

Hazardous Decomposition Products None			
Hazardous Polymerization	May occur	X	Rapid polymerization will occur in the presence of water, amines, alkalis and alcohol. Avoid skin contact.
	Will not occur		
Conditions of reactivity: Product can become unstable in the presence of polymerization initiators (water, amines alkali, etc.)			
Section VII – Spill or Leak Procedures			
Accidental Release Measures: Remove all ignition sources. Ventilate area, prevent product from entering drains. Flood with water to complete polymerization. Scrape off floor. Cured material can be disposed of as non-hazardous waste.			
Section VII – Special Protective Information			
Respiratory Protection (<i>Specify Type</i>) At high vapor concentrations, an approved self-contained breathing apparatus should be worn.			
Ventilation	Local Exhaust Positive down-draft exhaust ventilation should be provided to maintain vapor concentrations below established exposure limits.		Special None
	Mechanical Not Applicable		Other None
Protective Gloves Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.		Eye Protection Chemical splash goggles or safety glasses with side shields.	

Section IX – Special Precautions

Precautions: Keep away from heat, sparks, flames, and direct sunlight. Avoid contact with eyes, skin and clothing. Wear chemical resistant gloves when handling. Avoid inhalation of vapors.

Other handling information: Avoid contact with polymerization initiators such as water, alcohol, amines or alkali.

Storage information: Store in tightly closed, labeled containers at or below 75°F. Keep in well ventilated area away from heat, sparks and open flames.

Other Precautions:

Keep away from children. Avoid contact with skin and eyes. Avoid breathing vapors.

Section X – Regulatory Information

CERCLA/SARA Section 311/312: Immediate/Delayed health hazard, Fire, Reactive. WHMIS Hazard Class: B.3, D.2.B. All components are listed or are exempt from listing on the TSCA Inventory and the DSL.

Estimated HMIS Code: Fire Hazard (2) Health Hazard (2) Reactivity (1)

Section XI – Transportation Information

DOT (49CFR172):

Proper Shipping Name: Consumer Commodity

Hazard Classification: ORM-D

Unrestricted [Less than 450 L]

NA1993, Combustible liquid, n.o.s. (cyanoacrylate ester), 3, III [More than 450 L]

IATA:

Unrestricted [Not more than 500ml]

UN3334, Aviation regulated liquid, n.o.s., (cyanoacrylate ester), 9 [More than 500 ml]

Information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. Nothing herein shall be considered as recommending practices or products in violation of any patent, law or regulation. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. WE MAKE NO WARRANTIES REGARDING THE PRODUCTS AND DISCLAIM ALL EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.