

Material Safety Data Sheet U. S. Department of Labor

May be used to comply with Occupational Safety and Health Administration
OSHA's Hazard Communication Standard, (Non-Mandatory Form)
29 CFR 1910.1200. Standard must be Form Approved
consulted for the specific requirements. OMB No. 1218-0072

IDENTIFY (As used on label) NN Line Eliminator			
Section I			
Manufacture's Name PNI WorldWide		Emergency Telephone Number 1-800-535-5053 <small>(International Number)</small> 813-960-2780	
Address (Number, Street, City, State and ZIP Code) 5454 West Crenshaw Street		Telephone Number for Information SAA	
Tampa, FL 33634		Date Prepared 03/21/08	
Section II – Hazardous Ingredients/Identity Information			
Hazardous Components (Specify Chemical Identity: Common Name(s) OSHA PEL ACGIH TLV Other Limits Recommended % Optional)			
Ethyl Acetate 141-78-6 95-100%			
Warning! Flammable Liquid and Vapor			
Section III – Physical/Chemical Characteristics			
Boiling Point	172°F	Specific Gravity (H2O =1)	0.90 @ 20°C

Vapor Pressure (mm Hg)	75 @ 20°C	Melting Point	-117°F
Vapor Density (AIR = 1)	3.0	Evaporation Rate (Butyl Acetate = 1)	4.1
Octanol/Water Partition Coefficient	Log P = 0.73, P = 5.4	Autoignition temperature	905°F

Solubility in Water:
moderate @ 25°C

Appearance and Odor:
Clear liquid – sweet ester odor (threshold 3.9ppm)

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) -4°C (24°F)(T.C.C.)	Flammable Limits Ethyl acetate	LEL 2.0%	UEL 10.7%
--	-----------------------------------	-------------	--------------

Extinguishing Media:
CO₂, alcohol foam, dry chemical, water spray

Special Fire Fighting Procedures:
Wear self-contained breathing gear and protective clothing. Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting a fire and spread it.

Unusual Fire and Explosion Hazards:
Direct water jet will spread burning material. Danger or flashback exists if fumes reach a source of ignition. Cool sealed drums with water spray to lessen chance of rupture. Fumes are toxic.

Section V – Health Hazard Data

Threshold Limit Value:
OSHA (ethyl acetate) PEL 400PPM TWA; ACGIH, 400PPM TWA

Effects of overexposure:
Ingestion: irritating to gastrointestinal tract. Symptoms may include nausea, vomiting and diarrhea. Inhalation – may cause irritation of respiratory tract. Exposure to high concentrations may have a narcotic effect and may cause liver and kidney damage.

Skin and eyes – moderately irritating on contact. May cause redness and pain. Repeated contact with skin may cause cracking and Dermatitis.

Emergency and First Aid Procedures:

Ingestion: Give lukewarm water (pint). Do not induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Remove to fresh air (oxygen or artificial respiration if needed). Obtain medical attention if symptoms persist.

Skin: Wash with soap and water. Remove contaminated clothing and shoes. Seek medical attention if symptoms occur. Wash contaminated clothing before re-use. Discard contaminated shoes.

Eyes: Flush eyes with plenty of water for at least five minutes. Get medical attention if symptoms persist.

Section VI – Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (*Materials to avoid*)

Strong oxidizers, sources of ignition. Will attack some plastics.

Hazardous Decomposition Products:

Carbon Dioxide and Carbon Monoxide.

Hazardous Polymerization	May occur		Conditions to Avoid:
	Will not occur	X	

Section VII – Spill or Leak Procedures

Steps to be taken in case material is to be released or spilled:

Eliminate all sources of ignition. Permit only properly protected workers with skin and eye protection and self-contained breathing gear. Absorb small spills with non-flammable absorbent material and place in a container for chemical waste. Pump large spills into salvage tanks. Prevent runoff from entering drains, sewers or streams.

Waste Disposal Method:

Classified as hazardous waste under RCRA U112. Dispose in accordance with EPA and local regulations.

Section VIII – Special Protective Information

Respiratory Protection (*Specify Type*)

Above TLV. NIOSH/MESSA approved respirator. Compliance with OSHA standard 29CFR 16910.134

Ventilation Ventilation rates should be matched to conditions.	Local Exhaust Recommended	Special None
	Mechanical	Other None

Protective Gloves:

Resistant plastic or rubber

Eye Protection:

Chemical splash goggles recommended.

Other Protective Equipment:

Protective plastic or rubber apron.

Section IX – Special Precautions

Precautions to be taken in handling and storing:

Store in a cool, dry place in a tightly closed container.

Other Precautions:

Keep away from excessive heat and flame. Keep container closed when not in use. Keep well ventilated. Avoid contact with eyes. Avoid vapors. Keep away from children.

Section X – Toxicological Information

Acute Toxicity: Oral LD-50 (rat) 5.6g/kg; Inhalation LC-50 (rat) 16,000ppm/6 hours

Section XI – Regulatory Information

All ingredients are listed or exempt from listing on the TSCA Inventory

Estimated HMIS Code: Health Hazard (1) Fire Hazard (3) Reactivity (0)

Section XII – Transportation Information

DOT (49 CFR 172) UN#: 1173

Proper Shipping Name: Ethyl Acetate Packaging Group: II

Hazard Classification: 3 Hazard Label Required: Flammable Liquid

Information presented herein has been compiled from sources considered to be accurate and reliable, but is not guaranteed to be so. Nothing herein shall be considered as recommending practices or products in violation of any patent, law or regulation. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. WE MAKE NO WARRANTIES REGARDING THE PRODUCTS AND DISCLAIM ALL EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.