

MSDS - Material Safety Data Sheet

Emergency Phone Number:

Product Name: Peach Lotion

CHEMTREC: 1-800-424-9300

Manufacturer: Tammy Taylor Nails, Inc.
18007 Sky Park Cir., Suite E
Irvine, CA. 92614

949-250-9287

SECTION - I - PRODUCT IDENTIFICATION

DOT HAZARD CLASSIFICATION: Not Applicable

SECTION - II - COMPONENTS

INGREDIENT:	(BY WEIGHT)	PEL	TLV	CAS*
water	80%			
waxes				
Paraffin oil	10	5 mg/M3	5 mg/M3	8042-47-5
Vitamin E				
peach fragrance				
preservatives				

SECTION - III - PHYSICAL DATA

Boiling Point: 450°F (232.22°C) at 760 mm Hg
Vapor Pressure: Not Applicable
Specific Vapor Density: Not Applicable
Specific Gravity: .880 - .895 at 60°F (15.55°C)
Percent Volatiles: Not Applicable
Evaporation Rate: Not Applicable

SECTION - IV - FIRE AND EXPLOSION INFORMATION

Flashpoint (COC): 435°F (223.9°C)
Explosive Limit: Not Applicable
Extinguishing Media: Regular foam or CO2 or dry chemical.
Hazardous Decomposition Products: May form toxic materials; carbon dioxide and carbon monoxide, various hydrocarbons, etc.
Firefighting Procedures: Wear self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode when fighting fires. Water or foam may cause frothing, which can be violent and positively endanger the life of the firefighter, especially if sprayed into containers of hot, burning liquid. Water may be used to keep fire-exposed containers cool until fire is out.

NFPA CODES: Health-0 Flammability-1 Reactivity-0

SECTION - V - HEALTH HAZARD DATA

Permissible Exposure Level: 5 mg/M3
Threshold Limit Value: 5 mg/M3
Effects of Acute Overexposure:

Eyes - May cause irritation.

Skin - May cause irritation.

Breathing - of mist can cause irritation of nasal and respiratory passages.

Swallowing - can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Aspiration of material into the lungs can cause chemical pneumonitis, which can be fatal.

First Aid:

If on skin - Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use.

If in eyes - Flush with large amounts of water, lifting upper and lower lids occasionally, get medical attention.

If swallowed - Do not induce vomiting, keep person warm, quiet, and get medical attention. Aspiration of material into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal.

If breathed - Remove individual to fresh air.

SECTION - VI - REACTIVITY DATA

Hazardous Polymerization: Cannot occur.

Stability: Stable

Incompatibility: Avoid contact with strong oxidizing agents.

SECTION- VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:

Small Spill: Absorb liquid on paper, vermiculite, floor absorbent or other absorbent material.

Large Spill: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers. Prevent run-off to sewers, streams or other bodies of water.

Waste Disposal Method: Dispose in accordance with local, State and Federal regulations.

SECTION - VIII - PROTECTIVE EQUIPMENT TO BE USED

Respiratory Protection: NIOSH/MSHA approved air supplied respirator

Ventilation: General or local exhaust

Protective Gloves: Wear resistant gloves such as Neoprene

Eye Protection: Chemical splash goggles in compliance with OSHA regulations.

Other Protective Equipment: To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

SECTION - IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS

Handling and Storage: Avoid contact with eyes and prolonged or repeated contact with skin. Use or store only with adequate ventilation. Wear safety glasses or goggles, resistant gloves, and other appropriate protective equipment essential for your operation. Minimize exposure through good hygienic practices. Do not transfer to unlabeled container. Do not use cutting or welding torch on this container (even empty). For industrial use only.

This information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.